

cast iron **CENTRIFUGAL PUMPS**

Economical, general purpose centrifugal pumps can be used for water transfer, circulation, fountains, waterfalls, pressure boosting and sprinkling. Discharge can be rotated to horizontal or vertical installations.

FEATURES

- Capacities to 68 gallons per minute
- Ready-to-install 230 Volt motor -- see manual for 115 Volt conversion
- Heavy-duty motor
- Rugged, heavy-duty cast iron pump housing

FP5552

2 HP

Good 1 year warranty

FP5542

1-1/2 HP

Good 1 year warranty

FP5532

1 HP

Good 1 year warranty

FP5522

3/4 HP

Good 1 year warranty

FP5512

1/2 HP

Good 1 year warranty



PERFORMANCE INFORMATION

Rating	Model	HP	Motor Voltage	NPT Pipe Size		Discharge Pressure PSI (Pounds per Square Inch)							Maximum PSI
				Suction	Discharge	25	30	35	40	45	50	55	
Good	FP5552	2	115/230	1-1/2"	1-1/4"	68	62	54	48	38	29	7	57
Good	FP5542	1-1/2	115/230	1-1/4"	1"	59	52	47	40	30	15	-	51
Good	FP5532	1	115/230	1-1/4"	1"	47	40	35	29	17	-	-	49
Good	FP5522	3/4	115/230	1-1/4"	1"	31	25	21	13	-	-	-	43
Good	FP5512	1/2	115/230	1-1/4"	1"	22	13	2	-	-	-	-	36

*All performances shown in gallons per minute.

[Bombas de Agua Venezuela](#)

[Motores Electricos Venezuela](#)